

PRO SERIES

FOR THE REAL PROFESSIONALS


These machines were developed with specific goal, to be the best floor saw for the most demanding working conditions, the environment of rental shops.






NIC

RZ 120





TYPE	Dimensions (mm)					
RZ 120	Нмім	Нмах	W	Dміn	Dмах	
	950	1250	540	350	400	

TECHNICAL PAR	AMETERS	5
OPERATING PARA	AMETERS	
Weight	[kg]	100
Maximal cutting depth	[mm]	120/140
Blade diameter	[mm]	350/400
Blade connection	[mm]	25,4
Rpm w/o load	[rpm]	3400
Drive	[-]	Manual
Electric start	[-]	No
ENGINE	1	
Maker and type	Honda	GX270
Fuel	[-]	Petrol
Net power (3600 rpm)	[kW]	6,3
Cyclone filter	[-]	No
Emission class	[-]	EU Stage V
OPERATING F	LUIDS	
Water tank capacity (sprinkling)	[1]	20
Fuel tank capacity (petrol)	[1]	5,3
Engine oil capacity (10W30)	[U]	1,1
HYGIENIC PARA	METERS	
Noice level LpA,d	[dB]	101
Noice level Lwa, G	[dB]	110
Vibration ahvd	[m/s²]	12,5



FEATURES				
Frame design				
Lifting eye				
Brake				
Integrated sprinkling system				
Sealed bearings in the wheels				
Adjustable handle				
Safety pulley				

OPTIONAL ACCESSORIES	
Hour counter	0
Trottle levelron the control panel	0
Diamond blade for asphalt	0
Diamond blade for concrete and reinforced concrete	0

