

## **EASY SERIES**

**FLOOR SAWS** 

#### FOR SMALL PROJECTS AND HIGH MOBILITY


Light, compact and powerful, that is Easy series of floor saws, which are typically used for accompanying work on smaller projects.


#### **Cutting depth** Smooth lowering into the cut with an indicator and cut depth lock ensures Adjustable handle Lifting eye full control over the The height can be For easy handling. resulting cut. adjusted for the needs of operator. Sprinkling system Integrated with Compact water tank capacity dimensions 12 l and sprinkling For easy transport. on both sides of the blade. Engine Available with Honda GX series and Vanguard series. Handling points Located all around the machine for Smooth cut easy handling. Thanks to sealed bearings used for travel wheels **Closed frame** For maximum machine rigidity and engine protection.



# NIC

### **RZ 123**







TYPE	Dimensions (mm)			
RZ 123	Н	W	D	
	750	550	350	

TECHNICAL PARA	AMETERS				
OPERATING PARAMETERS					
Weight	[kg]	68			
Maximal cutting depth	[mm]	120			
Blade diameter	[mm]	350			
Blade connection	[mm]	25,4			
Rpm w/o load	[rpm]	3600			
Drive	[-]	Manual			
Electric start	[-]	No			
ENGINE					
Maker and type	Honda	GX200			
Fuel	[-]	Petrol			
Net power ( 3600 rpm )	[kW]	4,1			
Cyclone filter	[-]	No			
Emission class	[-]	EU Stage V			
OPERATING FLUIDS					
Water tank capacity (sprinkling)	[1]	12			
Fuel tank capacity (petrol)	[1]	3,1			
Engine oil capacity (10W30)	[1]	0,6			
HYGIENIC PARAMETERS					
Noice level LpA,d	[dB]	91			
Noice level Lwa,g	[dB]	105+4			
Vibration ahvd	[m/s²]	17,72+7,09			

FEATURES		
Frame design		
Lifting eye		
Handbrake		
Integrated sprinkling system		
Sealed bearings in the wheels		

OPTIONAL ACCESSORIES	
Hour counter	0
Diamond blade for asphalt	0
Diamond blade for concrete and reinforced concrete	0

