

EASY SERIES

FLOOR SAWS

FOR SMALL PROJECTS AND HIGH MOBILITY


Light, compact and powerful, that is Easy series of floor saws, which are typically used for accompanying work on smaller projects.


Cutting depth Smooth lowering into the cut with an indicator and cut depth lock ensures Adjustable handle Lifting eye full control over the The height can be For easy handling. resulting cut. adjusted for the needs of operator. Sprinkling system Integrated with Compact water tank capacity dimensions 12 l and sprinkling For easy transport. on both sides of the blade. Engine Available with Honda GX series and Vanguard series. Handling points Located all around the machine for Smooth cut easy handling. Thanks to sealed bearings used for travel wheels **Closed frame** For maximum machine rigidity and engine protection.



NIC

RZ 123V







TYPE	Dimensions (mm)			
RZ 123V	Н	W	D	
	750	550	350	

TECHNICAL PARAMETERS

	AMETERO				
OPERATING PARAMETERS					
Weight	[kg]	68			
Maximal cutting depth	[mm]	120			
Blade diameter	[mm]	350			
Blade connection	[mm]	25,4			
Rpm w/o load	[rpm]	3600			
Drive	[-]	Manual			
Electric start	[-]	No			
ENGINE					
Maker and type	Vanguard	GX200			
Fuel	[-]	Petrol			
Net power (3600 rpm)	[kW]	4,1			
Cyclone filter	[-]	No			
Emission class	[-]	EU Stage V			
OPERATING FLUIDS					
Water tank capacity (sprinkling)	[1]	12			
Fuel tank capacity (petrol)	[1]	3,1			
Engine oil capacity (10W30)	[1]	0,6			
HYGIENIC PARAMETERS					
Noice level LpA,d	[dB]	91			
Noice level Lwa, G	[dB]	105+4			
Vibration ahvd	[m/s²]	17,72+7,09			

FEATURES			
Frame design			
Lifting eye			
Handbrake			
Integrated sprinkling system			
Sealed bearings in the wheels			

OPTIONAL ACCESSORIES	
Hour counter	0
Engine wit cyclone filter	0
Diamond blade for asphalt	0
Diamond blade for concrete and reinforced concrete	0

