



FOR THE REAL PROFESSIONALS

These machines were developed with specific goal, to be the best floor saw for the most demanding working conditions, the environment of rental shops.







NTC STAVEBNÍ TECHNIKA SPOL. S.R.O. Jiřinková 120 552 03 Česká Skalice | Czechia WWW.NTC.CZ

NTC

FLOOR SAW | PRO SERIES







ТҮРЕ	Dimensions (mm)				
RZ 170	Нмім	Нмах	W	D	
	950	1250	540	450	

TECHNICAL PARAMETERS						
OPERATING PARAMETERS						
Weight	[kg]	110				
Maximal cutting depth	[mm]	170				
Blade diameter	[mm]	450				
Blade connection	[mm]	25,4				
Rpm w/o load	[rpm]	2800				
Drive	[-]	Manual				
Electric start	[-]	No				
ENGINE						
Maker and type	Honda	GX390				
Fuel	[-]	Petrol				
Net power (3600 rpm)	[kW]	8,7				
Cyclone filter	[-]	No				
Emission class	[-]	EU Stage V				
OPERATING FLUIDS						
Water tank capacity (sprinkling)	[1]	20				
Fuel tank capacity (petrol)	[1]	6,1				
Engine oil capacity (10W30)	[1]	1,1				
HYGIENIC PARAMETERS						
Noice level LpA,d	[dB]	92				
Noice level Lwa,g	[dB]	101+4				
Vibration ahvd	[m/s²]	5,22+2,09				



FEATURES				
Frame design				
Lifting eye				
Handbrake				
Integrated sprinkling system				
Sealed bearings in the wheels				

OPTIONAL ACCESSORIES	
Hour counter	0
Trottle levelron the control panel	0
Diamond blade for asphalt	0
Diamond blade for concrete and reinforced concrete	0

WWW.NTC.CZ



NTC STAVEBNÍ TECHNIKA SPOL. S.R.O. Jiřinková 120 552 03 Česká Skalice | Czechia