

These machines were developed with specific goal, to be the best floor saw for the most demanding working conditions, the environment of rental shops.



Lifting eye

For easy handling.

Adjustable handle

The height can be adjusted for the needs of operator.

Sprinkling system

Removable water tank with capacity 20 l and sprinkling on both sides of the blade.

Cutting depth

Smooth lowering into the cut with an indicator and cut depth lock ensures full control over the resulting cut.

Handling points

Located all around the machine for easy handling.

Engine

Available with Honda GX series, Vanguard series and Briggs&Stratton XR series.



Robust design



Ensures the highest durability and cut stability.

Smooth cut

Thanks to sealed bearings used for travel wheels.

Safety pulley

Three V-belts ensures the highest level of engine protection against overload.



TYPE	Dimensions (mm)			
	HMIN	HMAX	W	D
RZ 170B	950	1250	540	450

FEATURES
Frame design
Lifting eye
Handbrake
Integrated sprinkling system
Sealed bearings in the wheels

TECHNICAL PARAMETERS

OPERATING PARAMETERS		
Weight	[kg]	115
Maximal cutting depth	[mm]	170
Blade diameter	[mm]	450
Blade connection	[mm]	25.4
Rpm w/o load	[rpm]	2800
Drive	[-]	Ruční
Electric start	[-]	Ne

OPTIONAL ACCESSORIES

Hour counter	<input type="checkbox"/>
Trottle level on the control panel	<input type="checkbox"/>
Diamond blade for asphalt	<input type="checkbox"/>
Diamond blade for concrete and reinforced concrete	<input type="checkbox"/>

ENGINE		
Maker and type	B&S	XR 2100
Fuel	[-]	Benzin
Net power (3600 rpm)	[kW]	9,93
Cyclone filter	[-]	Ne
Emission class	[-]	EU Stage V

OPERATING FLUIDS		
Water tank capacity (sprinkling)	[l]	20
Fuel tank capacity (petrol)	[l]	6,6
Engine oil capacity (10W30)	[l]	1,1

HYGIENIC PARAMETERS		
Noice level L _{pA,d}	[dB]	94
Noice level L _{WA,G}	[dB]	107+4
Vibration a _{hvd}	[m/s ²]	5,22+2,09