



FOR THE REAL PROFESSIONALS

These machines were developed with specific goal, to be the best floor saw for the most demanding working conditions, the environment of rental shops.





TYPE	Dimensions (mm)				
	RZ 200B	HMIN	HMAX	W	DMIN
	950	1250	540	500	520

FEATURES
Frame design
Lifting eye
Handbrake
Integrated sprinkling system
Sealed bearings in the wheels

TECHNICAL PARAMETERS

OPERATING PARAMETERS		
Weight	[kg]	115
Maximal cutting depth	[mm]	190/200
Blade diameter	[mm]	500/520
Blade connection	[mm]	25,4
Rpm w/o load	[rpm]	2500
Drive	[-]	Manual
Electric start	[-]	No

OPTIONAL ACCESSORIES

Hour counter	<input type="checkbox"/>
Trottle level on the control panel	<input type="checkbox"/>
Diamond blade for asphalt	<input type="checkbox"/>
Diamond blade for concrete and reinforced concrete	<input type="checkbox"/>

ENGINE		
Maker and type	B&S	XR 2100
Fuel	[-]	Petrol
Net power (3600 rpm)	[kW]	9,93
Cyclone filter	[-]	No
Emission class	[-]	EU Stage V

OPERATING FLUIDS		
Water tank capacity (sprinkling)	[l]	20
Fuel tank capacity (petrol)	[l]	6,6
Engine oil capacity (10W30)	[l]	1,1

HYGIENIC PARAMETERS		
Noice level L _{pA,d}	[dB]	94
Noice level L _{WA,G}	[dB]	107+4
Vibration a _{hvd}	[m/s ²]	5,22+2,09